

ETT EB

Drawers-Automat



Sturdy plastic boxes are used to store high-quality individual items as well as inexpensive C-parts. The ETT EB boxes are available in four sizes for a wide range of applications.

The ETT EB impresses with its simplicity and universal application options.

Supported by the ATMS-CORE software and interlocked boxes, you can ensure your tool and measuring equipment management. This means that the products are available for use at all times. Thanks to the 'Control Top' add-on module with built-in PC and screen, every ETT EL can be used as a control unit.

Available as a control unit and extension unit

Standard colour: RAL7035 light grey and RAL7012 basalt grey


The ETT EB is made for:



Tools



Measuring device



Screw



Tensioning



Abrasive material



ETT EB

Technical Data:	EB-60	EB-76	EB-33	EB-44
Depth	725 mm	725 mm	725 mm	725 mm
Width	723 mm	723 mm	807 mm	731 mm
Height	1.272 mm	1.550 mm	1.550 mm	1.550 mm
Number of compartments	60	76	33	44
Own weight/load	175 kg / up to max. 5 kg	175 kg / up to max. 5 kg	175 kg / up to max. 5 kg	175 kg / up to max. 5 kg

Compartment type	Height (mm)	Width (mm)	Depth (mm)	Max. number of compartments per box	Total storage space (m ²)
EB-60	55	145	375	8	3,26
EB-76	55	145	375	8	4,13
EB-33	105	226	450	10	3,36
EB-44	105	142	470	10	2,94



ETT X'Tower

Variant	Number of compartments	Compartment size H0	Compartment size H1	Compartment size H2	Compartment size H2H	Compartment size H3	Compartment size H4
XTWR-1	324	0	12	48	0	264	0
XTWR-1-A	300	0	12	72	0	216	0
XTWR-1-B	468	0	12	72	0	48	336
XTWR-1-C	276	0	12	96	0	168	0
XTWR-1-D	444	0	12	96	0	0	336
XTWR-1-E	252	0	12	120	0	120	0
XTWR-1-F	228	0	12	144	0	72	0
XTWR-1-G	204	0	12	168	0	24	0
XTWR-1-H	288	0	24	24	0	240	0
XTWR-1-I	456	0	24	24	0	72	336
XTWR-1-J	264	0	24	48	0	192	0
XTWR-1-K	432	0	24	48	0	24	336
XTWR-1-L	240	0	24	72	0	144	0
XTWR-1-M	216	0	24	96	0	96	0
XTWR-1-N	192	0	24	120	0	48	0
XTWR-1-O	168	0	24	144	0	0	0
XTWR-1-P	228	0	36	24	0	168	0
XTWR-1-Q	204	0	36	48	0	120	0
XTWR-1-R	180	0	36	72	0	72	0
XTWR-1-S	156	0	36	96	0	24	0
XTWR-1-T	168	0	48	24	0	96	0
XTWR-1-U	144	0	48	48	0	48	0
XTWR-1-V	120	0	48	72	0	0	0
XTWR-1-W	108	0	60	24	0	24	0
XTWR-2	552	0	0	48	0	168	336
XTWR-2-A	528	0	0	72	0	120	336
XTWR-2-B	504	0	0	96	0	72	336
XTWR-2-C	504	0	0	96	0	72	336
XTWR-2-D	480	0	0	120	0	24	336
XTWR-2-E	360	0	0	72	0	288	0
XTWR-2-F	336	0	0	96	0	240	0
XTWR-2-G	312	0	0	120	0	192	0
XTWR-2-H	288	0	0	144	0	144	0
XTWR-2-I	264	0	0	168	0	96	0
XTWR-2-J	240	0	0	192	0	48	0
XTWR-2-K	216	0	0	216	0	0	0
XTWR-3	696	0	0	48	0	24	624
XTWR-3-A	720	0	0	48	0	0	672
XTWR-4	252	24	12	48	0	168	0
XTWR-4-A	372	24	12	48	0	48	240
XTWR-4-B	264	24	0	96	0	144	0
XTWR-4-C	216	24	24	24	0	144	0
XTWR-4-D	408	24	0	72	0	72	240
XTWR-5	324	0	12	24	24	264	0
XTWR-5-A	468	0	24	0	36	72	336
XTWR-5-B	540	0	0	24	36	144	336
XTWR-5-C	660	0	0	24	36	24	576
XTWR-5-D	456	0	12	24	144	240	36